



Amplified Telephone Ringer

FEATURES

- AC Powered via 12VDC Plug Pack
- Loud Ringing from an analogue line
- 101 Decibel Output Max. with Optional Horn Speaker
- Wall Mountable using standard telephone wall plate
- D.I.Y. Wall Mountable Template Supplied
- 12VDC Output to Drive Optional Strobe
- Visual Ring Indication
- Internal 10 Watt Mylar Speaker
- Adjustable Volume Control
- Adjustable Pitch control
- ACA/ACMA approved

Add extra loud ringing to any analogue phone

APPLICATIONS

- Suitable for The Hearing Impaired
- D.I.Y. Installation
- Single Line Loud Ringing
- Night Bell ringing
- Business / Offices / Warehouses
- Factories and Farms
- F



Optional 12 Volt DC Strobe

N1274



OPTIONAL ACCESSORIES



Amplified Telephone Ringer

SPECIFICATIONS

- Nominal Sound Pressure: 98 db @ 1 Metre from Internal Speaker
- Control Unit Dimensions: 112mm x 133mm x 58mm
- Optional External Speaker : 8 ohm, 10 to 15 Watt (Increases Output to 101db)
- 3 Metre Telephone Line Cord Supplied
- Power Supply 12VDC @ 1 Amp with 1.8 Metre Cord Included
- Connections: RJ12 6P2C for Line, 2.1 mm DC Socket
- Plugable Screw Terminal Connector for External Speaker and 12VDC Strobe

Add extra loud ringing to any analogue phone

